




DESIGNER AND MANUFACTURER OF CARGO RESTRAINT SYSTEMS



Web Winches

Ancra winches comply with DOT, WSTDA-T3 and Canadian Standard 905 regulations. Available in different base configurations to suit a variety of needs and load requirements.

All winches shown below are right hand models. Left hand models may be available on special orders. All winches shown below are bottom mount unless otherwise specified.

Black powder coat is the standard finish for all winches.



Seamless solid steel mandrel.

Powder coating withstands 250 hours of standard salt spray testing to ensure years of service.

Stamped working load limit and Ancra name certify quality.



43563-10
Standard Weld-On
Weight: 8.6 lbs./3.9 kg.
WLL: 5,500 lbs./2,500 kg.



43573-10
Storable Weld-On
Weight: 9.1 lbs./4.1 kg.
WLL: 5,500 lbs./2,500 kg.



43564-12
Standard Storable Portable w/ 2SS
Weight: 11.1 lbs./5. kg.
WLL: 5,500 lbs./2,500 kg.



43564-147
Standard Portable w/ 2SS Lighter 7mm heat treated frame
Weight: 7.7 lbs./3.5 kg.
WLL: 5,500 lbs./2,500 kg.



43579-20
Low Profile Side Mount Weld-On
Weight: 7.3 lbs./3.3 kg.
WLL: 5,500 lbs./2,500 kg.



43565-157
Standard C Track Slider Lighter 7mm heat treated frame
Weight: 7.6 lbs./3.5 kg.
WLL: 6,000 lbs./2,730 kg.



43565-127
Storable C Track Slider Lighter 7mm heat treated frame
Weight: 8.2 lbs./3.7 kg.
WLL: 6,000 lbs./2,730 kg.



49207-137
Standard Double L Track Slider Lighter 7mm heat treated frame
Weight: 6.5 lbs./2.9 kg.
WLL: 5,500 lbs./2,500 kg.



49207-187
Low Profile Double L Track Slider Lighter 7mm heat treated frame
Weight: 6.2 lbs./2.8 kg.
WLL: 5,500 lbs./2,500 kg.

Special Application Winches

Web Winches



48101-103
3-Bar Low Profile Side Mount Weld-On
Weight: 9.5 lbs./4.3 kg.
WLL: 6,000 lbs./2,730 kg.



49706-10
Standard Slider Wilson Track
Weight: 12.5 lbs./5.7 kg.
WLL: 5,500 lbs./2,500 kg.



49246-10-BP
Standard Slider Utility Trailer Track
Weight: 13 lbs./5.9 kg.
WLL: 5,500 lbs./2,500 kg.




41681-10
Standard Combination Weld-On
Weight: 10.6 lbs./4.8 kg.
WLL: 5,500 lbs./2,500 kg.

Combo Winch

SilverCap OverDrive Ratcheting Cap

PATENTED

Convert any winch into a ratcheting winch by adding Ancra's OverDrive Ratcheting Cap. The lubricated cap with a Grime Guard Weather-Tight Seal fits over the existing winch cap without having to remove the winch from the trailer, making it faster than conventional winches.



49723-10
Weight: 3.45 lbs./1.56 kg.



SilverCap OverDrive
Turns Any Winch Into A Ratcheting Winch






Winch Track

For standard C track and Double L track slider winches




42357-11

Steel C Track - Formed from high strength 1/4" steel plate
Weight: 39 lbs./17.73 kg.
Length: 6'



42357-21

Aluminum C Track - High strength aluminum extrusion
Weight: 19 lbs./8.64 kg.
Length: 6'



49242-10-120


Aluminum Double L Track - Designed for Double L slider winches. Weight: 26.25 lbs./11.92 kg. Length: 10'

PortaWinch

Versatile solution to turn stake pockets into anchoring points on flatbed trailers

PORTAWINCH™ (3-Bar Style)

PATENTED



49716-10

Standard outward off-set
Weight: 11.5 lbs./5.2 kg.
WLL: 5,500 lbs./2,500 kg.

49716-11

Inward off-set for track-mounted tarp clearance.
Weight: 11.5 lbs./5.2 kg.
WLL: 5,500 lbs./2,500 kg.

Covered by multiple U.S. and International Patents.

Ergo 360 Winch Bars

Easily rotates to any angle to provide the leverage needed to tension a strap



The Ergo 360 Bar is simply a better alternative to standard winch bars. The ergonomic design keeps the handle and tip in parallel alignment and in your "Power Zone" making it safer and easier to use. Available in 3 models standard, combination, and combination box end.



50015-10

Standard Ergo Bar, 34", Painted, Weight: 5.0 lbs./2.27 kg.



50015-20

Combination Ergo Bar, 34", Painted, Weight: 6.5 lbs./2.95 kg.



50015-21

Combination Box End Ergo Bar, 38-5/8", Painted, Weight: 6.0 lbs./2.72 kg.

Winch Bars

Tapered and angled at the end for easy operation, Ankra's winch bar handles are knurled at two sections, and the mushroom tip helps keep the bar from slipping from the winch cap. They are heat-treated for extra strength and cycle tested to simulate years of heavy use. Combination winch bars can be used to release tension on chain binders. Use caution to avoid injury. Not to be used as a cheater bar.



Flanged mushroom tip helps keep the bar from slipping from the winch cap.



42313-10

Standard Painted, Weight: 5.0 lbs./2.27 kg.



42313-12

Combination Box End, Painted Silver and Yellow, Weight: 6.5 lbs./2.95 kg.



42313-19

Combination Chrome, Weight: 6.5 lbs./2.95 kg.



42313-17

Standard Chrome, Weight: 5.0 lbs./2.27 kg.



Standard 2" Winch Strap WLL: 3,333 lbs./1,515 kg.



41659-10-27
27-ft. with Flat Hook

41659-10-30
30-ft. with Flat Hook



41659-13-27
27-ft. with Wire Hook

41659-13-30
30-ft. with Wire Hook

Standard 3" Winch Strap WLL: 5,400 lbs./2,450 kg.



41660-10-27
27-ft. with Flat Hook

41660-10-30
30-ft. with Flat Hook



41660-14-27
27-ft. with Chain Anchor

41660-14-30
30-ft. with Chain Anchor

Standard 4" Winch Strap WLL: 5,400 lbs./2,450 kg.



43795-10-27
27-ft. with Flat Hook

43795-10-30
30-ft. with Flat Hook



43795-11-27
27-ft. with Delta Ring

43795-11-30
30-ft. with Delta Ring



43795-13-30
30-ft. with Twisted Loop



43795-15-27
27-ft. with Chain Anchor

43795-15-30
30-ft. with Chain Anchor

Premium 4" X-TREME Winch Strap WLL: 5,400 lbs./2,450 kg.

Delivers greater abrasion resistance over conventional web straps

The ultimate winch straps for extreme applications. Ancra's new X-TREME webbing delivers greater durability, strength and abrasion resistance. Testing shows 80% retained strength over standard webbing.



43795-91-30
30-ft. with Delta Ring



43795-90-27
27-ft. with Flat Hook

43795-90-30
30-ft. with Flat Hook



43795-95-30
30-ft. with Chain Anchor



Roll-On/Roll-Off Container Strap 4" x 5-ft. with Container Hook-FMCSA Compliant



49526-10

4-in. x 5-ft. Strap w/ 48968-11 Container Hook.
WLL: 5,400 lbs./2,450 kg.



49526-11

4-in. x 5-ft. Strap w/ 48968-11 Container Hook and Sewn Loop end.
WLL: 5,400 lbs./2,450 kg.

Coil Racks Available in both light duty and heavy duty models for your specific applications



49344-10

Light Duty, 10 gauge steel, Weight: 5.7 lbs./2.60 kg.



49344-12

Heavy Duty, 1/4 steel sheet per ASTM A36, Weight: 15.63 lbs./7.09 kg.

Transport Chain

Grade 70 Transport Chain meets NACM standards

Chain Assemblies with Clevis Hooks



5/16" Chain Assemblies

45881-10-16 5/16" x 16" WLL: 4,700 lbs.

45881-10-20 5/16" x 20" WLL: 4,700 lbs.

45881-10-25 5/16" x 25" WLL: 4,700 lbs.

3/8" Chain Assemblies

45881-11-16 3/8" x 16" WLL: 6,600 lbs.

45881-11-20 3/8" x 20" WLL: 6,600 lbs.

45881-11-25 3/8" x 25" WLL: 6,600 lbs.

1/2" Chain Assemblies

45881-13-20 1/2" x 20" WLL: 11,300 lbs.

45881-13-25 1/2" x 25" WLL: 11,300 lbs.

Bulk Chain Clevis Hooks



5/16" Chain x 400'

45880-10 Wt: 408 lbs.

3/8" Chain x 200'

45880-11 Wt: 296 lbs.

1/2" Chain x 100'

45880-13 Wt: 251 lbs.

1/4" Chain x 400'

45880-12 Wt: 262 lbs.

5/16" Clevis Hook

45946-10 Wt: .85 lbs.

3/8" Clevis Hook

45946-11 Wt: 1.10 lbs.

1/2" Clevis Hook

45946-13 Wt: 2.10 lbs.

1/4" Clevis Hook

45946-12 Wt: .40 lbs.

Load Binders Drop forged steel meeting FMCSA and DOT specifications. In three popular models.

Lever Load Binders



45943-10

Accepts 5/16"-3/8" Chain
WLL: 5,400 lbs. Wt. 7.9 lbs.

45943-10HD HEAVY DUTY

Accepts 5/16"-3/8" Grade 70 Chain
WLL: 6,600 lbs. Wt. 9.4 lbs.

45943-11

Accepts 3/8"-1/2" Chain
WLL: 9,200 lbs. Wt. 11.9 lbs.

45943-13

Accepts 1/2"-5/8" Chain
WLL: 13,000 lbs. Wt. 20.8 lbs.

45943-12

Accepts 1/4"-5/16" Chain
WLL: 2,600 lbs. Wt. 3.5 lbs.

Recoilless Lever Load Binder



45943-14

Accepts 5/16"-3/8" Chain
WLL: 5,400 lbs. Wt. 9.0 lbs.

Lever Binder Locking Clip



50117-10

Securely Holds Binder Handle
Weight: .40 lbs./0.18 kg.

Ratchet Load Binders



45943-20

Accepts 5/16"-3/8" Chain
WLL: 5,400 lbs. Wt. 10.4 lbs.

45943-20HD HEAVY DUTY

Accepts 5/16"-3/8" Grade 70 Chain
WLL: 6,600 lbs. Wt. 10.5 lbs.

45943-21

Accepts 3/8"-1/2" Chain
WLL: 9,200 lbs. Wt. 11.8 lbs.

45943-23

Accepts 1/2"-5/8" Chain
WLL: 13,000 lbs. Wt. 15.7 lbs.

45943-22

Accepts 1/4"-5/16" Chain
WLL: 2,600 lbs. Wt. 3.57 lbs.



Ratchet Strap Assemblies Meets DOT and WSTDA T-1 standards for synthetic web tiedowns

2" Long-Wide Handle Ratchet Buckle Straps WLL: 3,333 lbs./1,515 kg.



45982-10
27 ft. with Flat Hooks

45982-11
30 ft. with Flat Hooks



45982-15
27 ft. with Chain Anchor

45982-34
30 ft. with Chain Anchor



45982-42
27 ft. with Wire Hooks

45982-43
30 ft. with Wire Hooks



45982-19
27 ft. with Twisted Snap Hooks

45982-36
30 ft. with Twisted Snap Hooks

3" Ratchet Buckle Straps WLL: 5,400 lbs./2,450 kg.



48987-20
27 ft. with Flat Hooks

48987-21
30 ft. with Flat Hooks



48987-24
27 ft. with Chain Anchor

48987-25
30 ft. with Chain Anchor

4" Ratchet Buckle Straps WLL: 5,400 lbs./2,450 kg.



49346-10
27 ft. with Flat Hooks

49346-11
30 ft. with Flat Hooks



49346-14
27 ft. with Chain Anchor

49346-15
30 ft. with Chain Anchor

Corner Protectors Full line of corner protectors to protect your straps and cargo



42098-11
Fiber Reinforced Rubber - For use with up to 3" web straps
Weight: .63 lb./ .29 kg.



42098-12
Fiber Reinforced Rubber - For use with up to 4" web straps
Weight: .75 lb./ .34 kg.



49584-10
12" Plastic - For use with up to 4" web straps
Weight: .47 lb./ .21 kg.



49377-10
Steel - For use with chain
Weight: 1.10 lbs./ .50 kg.



49577-10
Steel - For use with chain
Weight: .90 lb./ .41 kg.



49756-10
Steel - For use with chain and straps
Weight: 1.26 lbs./ .57 kg.




49377-11
Rubber Coated Steel
For use with chain and extends 4" to protect load.
Weight: 1.9 lbs./ .86 kg.



41516-11
Aluminum 6061-T6
Suitable for 2" webbing.
Weight: .63 lbs./ .29 kg.



43986-10
High Density Polymer - For up to 4" web straps
Weight: .06 lb./ .03 kg.



49913-10
Tarp Protector
Yellow plastic.
Weight: .21 lb./ .09 kg.

BE SURE YOU'RE SECURED If any part of the load securement system is loose — even if the required number of straps are used per regulation but are not tensioned properly — the load is considered unsecured. It is your responsibility to ensure the cargo is secure.




Ancra X-TREME - Engineered for Strength And Durability

Ancra Ratchet Buckle Strap Assemblies have redefined the industry standard. Now with the tested and proven 80% retained strength of Ancra X-TREME webbing and the integrity of our ratchet buckles, these assemblies surpass the others. A complete line of Ancra's standard and heavy-duty assemblies and accessories can meet all your specific requirements.

- Custom lengths and a wide range of end hardware are available
- Complies with WSTDA T-1 Standards
- Webbing meets or exceeds WSTDA T-4 Standards
- Standard fixed end length is 18-in., unless otherwise specified



Premium 2" X-TREME Ratchet Straps WLL: 3,333 lbs./1,515 kg.




45982-90-27

27 ft. with Flat Hooks


45982-90-30

30 ft. with Flat Hooks



45982-93-30

30 ft. with Chain Anchors



45982-95-27

27 ft. with Wire Hooks

45982-95-30

30 ft. with Wire Hooks

Web Keeper Ratchet Buckle




45982-90-27-WK

27 ft. Web Keeper with Flat Hooks

45982-90-30-WK

30 ft. Web Keeper with Flat Hooks

Premium 3" X-TREME Ratchet Straps WLL: 5,400 lbs./2,450 kg.




48987-90-27

27 ft. with Flat Hooks

48987-90-30

30 ft. with Flat Hook



48987-92-27

27 ft. with Chain Anchors

48987-92-30

30 ft. with Chain Anchors

Premium 4" X-TREME Ratchet Straps WLL: 5,400 lbs./2,450 kg.



49346-90-27

27 ft. with Flat Hooks

49346-90-30

30 ft. with Flat Hooks



49346-91-27

27 ft. with Chain Anchors

49346-91-30

30 ft. with Chain Anchors



49346-93-27

27 ft. with Wire Hooks

49346-93-30

30 ft. with Wire Hooks

Top Premium Brand Tarp Ties

Made in the USA and known for quality, durability, and resistance to the elements, these tarp ties offer good stretch recovery and maintain their strength over the entire life of the tarp ties. The two lines include the longest lasting, larger cross section Goldline® Heavy Duty EPDM tarp ties best recognized by truckers, and the standard cross section Silverline Elite® EPDM. Our natural rubber tarp ties are best suited for colder climates and are our most economical offering. Ancra's tarp tie offering provides you the customer with product options that can be chosen and suited to your application.



- Quantity 50 per box
- Designed to hold tarp covers on trucks and trailers
- Not to be used to restrain or secure cargo
- Wear safety glasses and use caution when using tarp ties
- Molded EPDM construction for high Ozone resistance and strength resiliency or molded natural rubber for good cold weather stretch properties

**Truckers Choice
for Over 40 Years!**

GOLDLINE®
Made in USA

SILVERLINE®
ELITE
EPDM
Made in USA

**NATURAL
RUBBER**

52210GL

10" Goldline HD EPDM

52215GL

15" Goldline HD EPDM

52221GL

21" Goldline HD EPDM

52231GL

31" Goldline HD EPDM

52241GL

41" Goldline HD EPDM

52210SE

10" Silverline Elite EPDM

52215SE

15" Silverline Elite EPDM

52221SE

21" Silverline Elite EPDM

52231SE

31" Silverline Elite EPDM

52241SE

41" Silverline Elite EPDM

52210C

10" Natural Rubber

52215C

15" Natural Rubber

52221C

21" Natural Rubber

52231C

31" Natural Rubber

52241C

41" Natural Rubber

X-TREME GUARD™

Ancra's new high-density polyethylene X-TREME GUARD™ Corner Protector distributes strap tension over the length of the guard to prevent your cargo from being crushed by the straps and protects your webbing from cuts and abrasion. Made in lengths of 12-, 24-, 36- and 48-inches, this durable guard is strong yet lightweight, and crack/ weather resistant to -30°.

- Constructed of High Density Polyethylene for strength and durability
- Protect cargo from being crushed by the straps and the webbing from cuts and abrasion
- Spread the strap tension over the length of the guard
- More durable than wood and greater memory than aluminum
- Weather and UV resistant, Good to -30°F
- Made from recycled materials



50089-12

8' x 1' long
Weight: .8 lbs./ .36 kg.



50089-24

8' x 2' long
Weight: 1.7 lbs./ .78 kg.



50089-36

8' x 3' long
Weight: 2.7 lbs./ 1.23 kg.



50089-48

8' x 4' long
Weight: 3.6 lbs./ 1.63 kg.



Flags & Banners Meets FMCSA 393.87 Standards



49894-10

Wide Load/Oversize Load, 2-sided,
84" x 18" Vinyl
Yellow with four 44" ropes & grommets

49894-12

Wide Load/Oversize Load, 2-sided,
72" x 14" Vinyl
Yellow with four 44" ropes & grommets



49894-11

Wide Load/Oversize Load, 2-sided,
84" x 18" Vinyl
Yellow with four grommets, Sewn in Ropes,
Top and Bottom



49894-13

Oversize Load Mesh Sign, Single Sided
84" x 18" Polyester
Yellow with 4 grommets and four 44" ropes

49894-14

Wide Load Mesh Sign, Single Sided
84" x 18" Polyester
Yellow with 4 grommets and four 44" ropes



49895-10

Canadian "D" Sign
96" x 12"
Red/White Vinyl
10 Grommets



49893-10

Flourescent Red Safety Flag
18" x 18"
Heavy Duty Mesh
Wooden dowel




49893-11

Red Safety Flag
18" x 18"
Cotton
Steel wire rod



49893-12 49893-14

Flourescent Red (-12) or Orange (-14)
Safety Flag
18" x 18"
Heavy Duty Mesh
2 brass grommets



49893-13

Flourescent Orange
Safety Flag
18" x 18"
Heavy Duty Mesh
Wooden dowel

Web Winders Rolls all your winch straps neatly and quickly. Helps to extend the life of your winch straps.



50092-10

EZ Winder Strap Winder quickly and easily
winds webbing onto your winch for storage.



50391-10

Premium Cargo Strap Winder
Constructed of zinc-plated steel for maximum durability,
the new Strap Winder quickly assists in winding winch
straps into rolls for storage. Designed to clip into trailer
stake pocket or side rail.
Weight: 2.7 lb./1.2 kg.





Lift-A-Deck

THE DECK SYSTEM SPECIALISTS

Decking System

PATENTED

U.S. Patent No. 6,074,143

The most popular patented solution for decking loads in trailer and van bodies. With Ancra's patented adjustable second deck in your trailer, you can carry double the amount of palletized freight, or you can mix loads with only part of the vehicle double decked. The Ancra Lift-A-Deck® II system is the most versatile you can install. With many track styles to choose from, installations can be made on any type of vehicle construction.



Standard & Low Profile Beams w/ Low Profile Foot and Channel Assembly



49414-15

Standard LAD Beam
Adjustment range: 95.1" - 105.6"
Weight: 18.1 lbs./8.2 kg.
Decking WLL: 2,200 lbs./999 kg.
Shoring WLL: 2,200 lbs./999 kg.

49414-19

Heavy Duty LAD Beam
Adjustment range: 95.1" - 105.6"
Weight: 19.7 lbs./8.9 kg.
Decking WLL: 3,000 lbs./1,360 kg.
Shoring WLL: 2,500 lbs./1,135 kg.

Wide Top Beam w/ Low Profile Foot and Channel Assembly

The textured Beam top surface is 4-1/2" wide to increase the contact area for cargo on the beam deck.



50080-11

Wide Top LAD Beam Assembly
Adjustment range 95.1" - 105.6" / Weight: 24.9 lbs./11.3 kg.
Decking WLL: 4,000 lbs./1,816 kg. Not recommended for shoring.

PATENTED



Poly Deck Board

- Lighter than plywood - Increase trailer capacity
- Ergonomic - Convenient hand slot
- Stackable - Nests for storage
- Durable - Reduces purchase frequency
- Recyclable - Energy savings



50105-11

For beams set at 16" & 24" centers.
48" x 48" x 2.7"H / Weight: 21 lbs./9.53 kg.

Lift-A-Deck II Track Options - Other Track Styles Available



50072-14-72.00


Flanged Double Track
Beveled, Weight: 6.8 lbs./ 3.1 kg.



50058-18-72.00

Flanged Single Track
Beveled, Weight: 4.2 lbs./ 1.9 kg.

Beam Release Bar



49445-12

Length: 52 inches. Weight: 2.5 lbs./1.14 kg.

Lift-A-Deck II Logistic Straps



12-ft. 16-ft. 20-ft.
40602-100 40602-101 40602-102
6,000 lb. Polyester Webbing with
Cam Buckle and Single Stud Fitting.
Working Load Limit: 833 lbs./378 kg.



12-ft. 16-ft. 20-ft.
48672-16 48672-17 48672-18
6,000 lb. Polyester Webbing with Ratchet
Buckle and Double Stud Fitting. Fixed End: 48-in.
Working Load Limit: 1,500 lbs./680 kg.

Beam Release Bar Holder



50055-10

Weight: .44 lbs./ .2 kg.



Logistic Track

Ankra Series E, A and F Track were designed to team with Ankra end fittings, Beam Sockets, and Decking/Shoring Beams for the strongest, most reliable support. Steel constructed and tested for strength, Ankra Track comes in 10 ft. (3 m) lengths for a wide range of cargo restraint applications. To withstand corrosion, Ankra galvanized track has a G-90 hot dip finish with a surface chemical treatment.

Series E Logistic Track - Made with high grade 12-gauge steel



48117-25-120.00

Gray Powdercoat

Weight: 16.6 lbs./7.5 kg.
Length: 10 ft./3 m.

48117-25-60.00

Gray Powdercoat

Weight: 8.3 lbs./3.77 kg.
Length: 5 ft./1.5 m.



48117-21-120.00

Galvanized

Weight: 17.2 lbs./7.80 kg.
Length: 10 ft./3 m.

48117-21-60.00

Galvanized

Weight: 8.6 lbs./3.90 kg.
Length: 5-ft./1.5 m.



48117-32-120.00

Black Powdercoat

Weight: 16.6 lbs./7.5 kg., Length: 10 ft./3 m.

Vertical

40838-10


Gray Powdercoat

Weight: 13.5 lbs./6.1 kg.
Length: 10 ft./3 m.


40838-11

Galvanized

Weight: 14 lbs./6.4 kg.
Length: 10 ft./3 m.



Series F Logistic Track



40849-14

Galvanized 1.62 in. hole spacing & 3/4" hole dia.
Weight: 6.0 lbs./2.7 kg., Length: 10 ft./3 m. 15-gauge.



49313-13

Galvanized 1.62 in. hole spacing.
Weight: 12.2 lbs./5.53 kg., Length: 10 ft./3 m. 12-gauge.

Series A Logistic Track



42948-10

Gray Powdercoat

Weight: 15.0 lbs./6.8 kg., Length: 10 ft./3 m. 12-gauge.



49359-10

Aluminum

Weight: 8 lbs./3.6 kg., Length: 10 ft./3 m.

Shoring Bars – F Series with new easy push button design

Round Shoring Bar



Square Shoring Bar



Adjustable in 2 in. increments with recommended install length of 81-117 in.



49439-10

For 3/4-in. hole diameter track (U.S.)
Shoring WLL: 500 lbs./227 kg., Wt: 20.0 lbs./9.1 kg.

49439-11

For 1-in. hole diameter track (Canada)
Shoring WLL: 500 lbs./227 kg., Wt: 20.0 lbs./9.1 kg.



49439-20

For 3/4-in. hole diameter track (U.S.)
Shoring WLL: 1,000 lbs./454 kg., Wt: 28.0 lbs./12.71 kg.

49439-21

For 1-in. hole diameter track (Canada)
Shoring WLL: 1,000 lbs./454 kg., Wt: 28.0 lbs./12.71 kg.



Series E and A Decking/Shoring Beams with Patented Flat Latch

PATENTED U.S. Patent No. 6,895,867

All Ankra Decking/Shoring Beams are equipped with our patented Flat Latch. The Flat Latch eliminates bent triggers, jammed beams, costly beam replacement and repairs, and out-of-service problems. The Flat Latch can't damage interior trailer walls. The flat latch channel assembly can be purchased separately to retro-fit older trigger style beams.



Flat Latch

Standard Duty Aluminum E and A Decking Beams - Decking & Shoring WLL: 2,200 lbs.

43638-50 Adjustment range 85.7-96.6 in. Wt: 16.0 lbs./7.3 kg.

43638-51 Adjustment range 92.9-103.8 in. Wt: 18.8 lbs./8.5 kg.

Heavy Duty Aluminum E and A Decking Beams - Decking WLL: 3,000 lbs. Shoring WLL: 2,500 lbs.

49039-50 Adjustment range 84.7-95.6 in. Wt: 20.5 lbs./9.3 kg.

49039-51 Adjustment range 92.9-103.8 in. Wt: 22.5 lbs./10.2 kg.

49039-52 Adjustment range 93.8-106.9 in. Wt: 24.25 lbs./11.0 kg.

Cargo Sta Load Bars - Available in Aluminum and Steel Bar models for light to medium duty applications. Bolt-On Feet



Aluminum Cargo Sta

43782-15 6061 T6 Aluminum, Length/Weight: 89.75 - 104.5 in. 8.95 lbs./4.07 kg. Long Tube Diameter: 1.50 in.

Steel Cargo Sta

48407-10 Galvanized Steel Tubing, Length/Weight: 89.75 - 104.5 in. 11.72 lbs./5.33 kg. Long Tube Diameter: 1.50 in.

Jack Bars - Ankra's jack mechanism makes quick work of securing loads and is available in three models for light to medium duty applications.




Heavy Duty One-Piece - Galvanized finish for corrosion resistance.

49205-25 Weight: 16.2 lbs./7.35 kg. Adjustment range: 85.0" - 104.0" Black Handle

49205-26 Weight: 16.6 lbs./7.54 kg. Adjustment range: 85.0" - 114.0" Red Handle

Heavy-Duty One-Piece Jack Bar with Hoops -

Built-in hoops for restraining small items and packages. One-Piece Galvanized



49205-27

Weight: 20.0 lbs./9.08 kg. Adjustment range: 85.0" - 114.0" Red Handle

49205-28

Weight: 19.6 lbs./9.0 kg. Adjustment range: 85.0" - 104.0" Black Handle

Universal Jack Bar - This jack bar features a patented design which allows for 3 adjustment range settings, increasing its versatility for use in half load applications.



Patented Safety Snap Pin




49205-31 Adjustment range- Fully extended: 85-114-in. Mid extension: 70-99-in. Fully retracted: 51-80-in.

Weight: 18.2 lbs./8.26 kg. **PATENTED** U.S. Patent No. 6,736,371.



Accessories



43991-10

Cargo Sta Hoop Set

Designed to help restrain the movement of small packages of cargo within your truck or trailer. For 43782 and 48407 round tube bars. Tube Diameter: 1.5 in. Weight: 10.0 lbs./4.5 kg.



49348-11

Bar Keep Cargo Bar Holder

Constructed of high quality steel and finished with black powder coating for corrosion resistance. Holds two standard or heavy-duty cargo bars. Weight: 6.68 lbs./3.03 kg.



40921-10

Standard Beam Socket


For use w/ commercial grade Douglas Fir 2"x6" lumber. Weight: .70 lb./32 kg.



40921-11

Heavy-Duty Beam Socket

For use w/ commercial grade Douglas Fir 2"x6" lumber. Internally welded plate for added strength. Weight: .85 lb./39 kg.



43627-13

Replacement Channel Assembly

With patented flat latch. 11 Gauge. For aluminum beams 43638, 49039 and 50158. Weight: 3.8 lbs./1.73 kg.



40386-11

Series E/A Rope Tie Off

With spring actuated fitting for rope use in Series E or A track WLL: 1,333lbs./605 kg. Weight: .40 lbs./18 kg.



10902-11

36 in. / User Weight Limit: 320 lbs.



Driver Assist Strap

Helping Hand. Ancra's Driver Assist Strap lends a hand to drivers and dock workers climbing into and out of trailers. The 36" strap with reinforced handle connects to existing E or A track, offering a convenient additional hand grip for a more secure entry and exit. Assembled with high strength components for a rated user weight limit of 320 lbs. Patent pending.

Series E Cam Buckle Straps with Spring End Fittings

Popular straps for securing light to medium loads. Comes in 3 color coded sizes. **WLL: 833 lbs./378 kg.**



40602-17

12 ft, - Yellow Webbing. Weight: 1.65 lbs.



40602-18

16 ft, - Gray Webbing. Weight: 1.80 lbs.



40602-19

20 ft, - Blue Webbing. Weight: 1.95 lbs.

Series E Ratchet Buckle Straps with Spring End Fittings

Low profile ratchet buckle makes tensioning more convenient for securing loads. Three standard color coded sizes. **WLL: 1,333 lbs./605 kg.**



48672-13

12 ft, - Yellow Webbing. Weight: 2.25 lbs.



48672-14

16 ft, - Gray Webbing. Weight: 2.40 lbs.



48672-15

20 ft, - Blue Webbing. Weight: 2.55 lbs.


Torque Limiting Ratchet Straps with Spring End Fittings

Reduces the possibility of damage to logistics track and sidewalls by limiting the pre-load torque placed on the strap assembly. Patented ratchet mechanism limits strap tension to 300 lbs., enough to secure your load, but not enough to cause damage from over tightening. **WLL: 1,333 lbs./605 kg**



48672-33

12 ft, - Yellow Webbing. Weight: 2.50 lbs.



48672-34

16 ft, - Gray Webbing. Weight: 2.65 lbs.




48672-35

20 ft, - Blue Webbing. Weight: 2.80 lbs.



Utility Tiedowns – Versatile and reliable for securing a wide range of light- to medium-duty cargo.



41048-10
Cam Buckle Tiedown
1" x 5-1/2' Red
Vinyl Coated S Hooks
Fixed End: 6 in.
WLL: 400 lbs./181 kg.
Weight: 1.60 lbs./.73 kg.



43887-10
Mini Ratchet Strap with D-Ring and Wire Hooks
WLL: 1,000 lbs./454 kg.
1" x 16'
Weight: 1.56 lbs./.71 kg.
43887-11 1" x 20'
Weight: 1.69 lbs./.77 kg.



49368-10
Ratcheting Tiedowns
1" x 15' 4-pack
1" red Ratchet strap with vinyl-coated S Hooks secures cargo, equipment and household furnishings.
Weight: 4.7 lbs./2.14 kg.
WLL: 266 lbs./121 kg.



49368-11
Cam Buckle Tiedowns
1" x 6' 4-pack
1" black Cam strap with scratch-resistant vinyl-coated S Hooks. A simple way to secure your possessions.
Weight: 3.7 lbs./1.69 kg.
WLL: 266 lbs./121 kg.



49368-12
Combo 4 Pack
Contains two each 1" multipurpose Ratchet and Cam Buckle tie downs with scratch-resistant vinyl coating.
Weight: 4.2 lbs./1.91 kg.
WLL: 266 lbs./121 kg.



95002
Ratcheting Tiedowns
1" x 10' 2-pack
1" black Ratchet straps with vinyl-coated S Hooks in an interactive package.
Weight: 2.25 lbs./1.0 kg.
WLL: 550 lbs./250 kg.



95007
Ratcheting Tiedowns
1" x 12' Endless Loop, 2-pack, 1" Ratchet straps in an interactive package.
Weight: 1.75 lbs./.79 kg.
WLL: 550 lbs./250 kg.



95003
Retractable Ratcheting Tiedowns
1" x 6' 2-pack
1" black Retractable Ratchet straps with scratch-resistant vinyl-coated S Hooks in an interactive package.
Weight: 3.20 lbs./1.45 kg.
WLL: 500 lbs./227 kg.



95004
Cam Buckle Tiedowns
1" x 8' 4-pack
1" red Cam straps with scratch resistant vinyl-coated S Hooks in an interactive package.
Weight: 3.8 lbs./1.72 kg.
WLL: 400 lbs./180 kg.



95005
Ratcheting Tiedowns
1" x 10' 4-pack
1" black Ratchet straps with vinyl-coated S Hooks in an interactive package.
Weight: 4.6 lbs./2.1 kg.
WLL: 550 lbs./250 kg.



49603-10
TrackStar Motorcycle Wheelchock
Quick Connect to aircraft style L track. Fits tire widths from 3.5" to 5.5". Comes complete with mounting kit.
Weight: 7.0 lbs./3.18 kg.



Specifications


Working Load Limit (WLL)

The maximum load a component or assembly should be subjected to during routine use.

Rated Load Capacity

Ratings are generally established and/or regulated by industry or legislative standards and may vary from industry to industry. The working load limit rating (WLL) is established by Federal DOT Standards at 1/3 of the Breaking Strength of the assembly.

Note: All strengths referenced in this brochure unless noted, are based on a straight pull application.



IMPORTANT NOTE:

It is the owner's and user's responsibility to determine suitability of a product for any particular use. Check all applicable industry, trade association, federal, state and local regulations. Read all operating instructions and warnings carefully.

All ratings shown in this catalog are based on the product being new, and used in normal environmental conditions. Special consideration must be given to item selection when unusual conditions can be expected. Particular caution should be exercised to avoid exposing the product to sharp edges, acids, alkalis and temperatures above 194°F.

Products are subjected to age, wear, and deterioration, all of which cause a reduction in the product's working load limit. We recommend that all products be regularly inspected. Any worn, deformed, misused or overloaded products should be replaced.

CAUTION! The component with the lowest working load capacity in the entire restraint system will determine its strength. Each component of the entire system plays an important part in restraining cargo. It is important that tie downs be attached to anchorage that are of sufficient strength to properly secure the load. For example, if one anchors a standard web binder assembly with a rated WLL of 5,000 lbs. to a device with a WLL of 1,000 lbs., then that system is only as good as the anchorage and would be limited to a 1,000 lbs. capacity WLL.

The purpose of this catalog is to assist our customers in the selection of cargo restraint products suitable for their specific applications. Because we continuously strive to offer new and improved products, part numbers and specifications are subject to change without notice. Please contact your Ancra Representative or our Customer Service Department for any new information.