

AIR FILTER CLEANING

Guideline

MOTOLINE

EN Whether it is the finest sand or coarse mud, your motorcycle's air filter has to do a good job in order to protect the engine from the smallest pollutants.

Cleaning and maintenance require special attention so that the filter can always breathe free. You do not have to be a professional mechanic to carry out this work. Our maintenance manual, which contains all sorts of professional tips, allows you to clean filters simply and efficiently. All of the experience which MOTOREX has gained through working with international racing teams and leading companies in the motorcycle industry is reflected in the maintenance and cleaning products for foam air filters.

Take advantage of this expertise to ensure your motorcycle has a long lifetime and performs optimally.

CONTENT

SAFETY	4
AIR FILTER CLEANING KIT	5
OFF ROAD BY MOTOREX	6-7
CLEANING	9 – 10
RINSING	10 – 11
LUBRIFICATING	13 – 14
GREASING	14 – 15
FITTING	16 – 17
MORETIPS	18
MISCELLANEOUS	19

SAFETY

- Wear disposable latex gloves during the entire process.
- We recommend that you wear goggles.
- Do not pour the products down the sink; dispose of them correctly.
- Please note that if possible all these operations should be carried out in a very well-ventilated area or, even better, in the open air.



AIR FILTER CLEANING KIT

 Complete air filter cleaning kit, essential equipment for all-terrain use. Simple, practical and effective.

OFF ROAD BY MOTOREX



MOTOREX foam filters for every type



AIR FILTER CLEANER

Cleaner for foam air filter elements





AIR FILTER OIL 206

AIR FILTER

MOTOREX

 Oil for foam air filter elements with good adhesion

11, 51,



AIR FILTER OIL SPRAY

 Air Filter Oil Spray for foam air filter elements with good adhesion

Spray: 750 ml



RACING BIO LIQUID POWER



Biodegradable air filter oil



MOTOREX

RACING BIO DIRT REMOVER

Rapidly biodegradable cleaner for air filters 900g



CLEANING

EN After you have removed the contaminated air filter, pour approximately 2-3 litres of MOTOREX AIR FILTER CLEANER into a large bucket. Fully immerse the filter and leave the cleaner to work for approximately 5-10 minutes. Then squeeze the filter until it is completely clean, both inside and outside. When doing this, use disposable latex gloves to protect your hands.

Our tip: Be extremely careful when squeezing the filter to ensure that you do not damage the foam.













RINSING

EN Rinse the filter well under running water and squeeze it several times like a sponge. If, after rinsing, you see any stubborn stains which were there before, repeat the cleaning and rinsing process. When doing this, ensure that the filter is squeezed thoroughly and there is almost no water in the filter.

Our tip: Place the washed filter in a cotton cloth and squeeze it again. Never wring or twist the filter. Then leave the filter to dry out completely. Please note that using a hairdryer will damage the pores and the adhesive.



LUBRICATING

EN Pour the MOTOREX AIR FILTER OIL 206 into a small bucket. Do not immerse the filter completely in the oil, but selectively dab it with the oil. Now carefully rub the absorbed oil into the filter. If necessary, dab the filter again with a small amount of oil until it is completely and evenly oiled. Even when using the MOTOREX AIR FILTER OIL SPRAY, the oil must be rubbed into the filter.

Our tip: When oiling, the following motto applies: As little as possible, as much as necessary. The filter must not drip after being oiled. Leave the filter to dry out thoroughly after being oiled. 24 hours is ideal













GREASING

EN Before fitting the filter, you should grease its contact surface with MOTOREX Grease 2000. The reason for this is to seal the foam filter and the housing since the smallest contamination particles can penetrate at this point.

Our tip: Do not apply too much grease, but apply it evenly.



FITTING

EN When riding off-road, a light oil film is deposited in the air filter box which also binds dirt. You should clean the air filter box with MOTOREX POWER BRAKE CLEAN so that the filter can be used in a clean condition.

Our tip: Thoroughly rub the air filter box dry after cleaning. Check that the air filter has been fitted correctly after installation.







MORE TIPS

- All the MOTOREX products used in the instructions can be used again the next time you maintain your filter.
- Always keep the oiled filter away from light, ideally in a plastic bag. Nevertheless, ensure that it is sufficiently ventilated.
- Take the opportunity to maintain several foam filters at the same time. This gives you longer riding pleasure and the filters can be left to dry out for an appropriate length of time.

MISCELLANEOUS





MOTO CLEAN (360°)

The motorcycle cleaner with power

11, 51



 Quick cleaner with water-beading effect. Spray: 500ml, 51



MOTO PROTECT (360°

 Maintenance and protective spray Spray: 500ml



CHAIN LUBE OFF ROAD

 Fully synthetic chain lubricant Spray: 56ml / 500ml



BUCHER AG LANGENTHAL

EN For 100 years, the largest independent oil blending company in Switzerland, with it's headquarters in Langenthal in the heart of Switzerland, has been active in research, development and production of innovative lubricants and chemicals, which are established on the world market. Every day, experienced tribology specialists, engineers, chemists, technicians and marketing specialists devote their efforts to helping MOTOREX maintain it's position as a market leader.

MOTOREX products are subject to a continuous process of research and development. BUCHER AG LANGENTHAL therefore keeps the rights to change all technical data contained in this brochure at any time and without previous notice. Under reserve of errors and misprints.

